FEMTO R

1.180

Allowed user weight

125 kg

Suitable for passenger transport



MEYRA GROUP

Fuse Together

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Low wear due to high quality attachments

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- Adaptable to functional changes and individual needs of the user through adjustment of the back, seat and chassis
- Extensive equipment assortment for long-term users

FIELD OF USE

- For permanent and long term provision
- For paraplegic provision
- Very good suitability for many disease patterns, even for severely encumbered
- Users without function of the lower extremities (lateral transfer, driven through the handrims)

● ORDER ○ COST ESTIMATE ○ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Price basic model ***3.298,00 €***

Allowed user weight
125 kg

Suitable for passenger transport

Hints
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.

ACTIVE

Technical specifications

Seat widths in mm	320/340/360/380/400/420/440/460/480/500
Width ready to drive in mm from	510 - 810
Seat depth in mm	340/360/380/400/420/440/460/480/500
Seat height front/rear in mm	450 to 530 / 390 to 500
Overall height in mm	Rear seat height + back support height
Back support height in mm	variable from 250 to 450 +/- 15
Length with footrest in mm	760 - 860 (depending on frame length, wheel size)
User weight	125 kg
Empty weight from	from 8,5 kg
Permitted total weight in kg	140 kg
Transport weight	from 5.6 kg
Rear wheel	600 mm(24 inch) / 635 mm(25 inch) / 660 mm(26 inch)
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

01 Frame

	CODE	DESCRIPTION	ANGLE	EUR €
❑	346	Standard front frame	80°	0,00
❑	347	Compact front frame	88°	0,00

Frame options

	CODE	DESCRIPTION	EUR €
❑	4959	Without taper frame ⚠ *NC with seat width > 460mm (C-48, C-350)*	0,00
❑	4950	Taper frame (20 mm each side) ⚠ *NC with seat width < 380mm (C-32, C-34, C-36)*	0,00

Frame Colours

	CODE	DESCRIPTION	EUR €
❑	130	Titanium grey	0,00
❑	206	Matt black	0,00
❑	224	Blue metallic	0,00
❑	227	Red metallic	0,00
❑	4044	Red matt	0,00
❑	4049	Olive green matt	0,00
❑	4050	Skyblue	0,00
❑	4051	Chalk	0,00
❑	4922	Metallic green	0,00
❑	4919	Silverline	0,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

02 Seat Width (SW) / Seat Depth (SD)

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Seat depth is measured from the front of the backrest tube to the front edge of the seat upholstery.

	Frame Length S / M						Frame Length L		
	C-394	C-366	C-368	C-615	C-784	C-618	C-619	C-787	C-792
	SD 340mm	SD 360mm	SD 380mm	SD 400mm	SD 420mm	SD 440mm	SD 460mm	SD 480mm	SD 500mm
C-32 SW 320mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-34 SW 340mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-36 SW 360mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-38 SW 380mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-40 SW 400mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-342SW 420mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-344SW 440mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-46 SW 460mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-48 SW 480mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-350SW 500mm	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00

Frame Length

FSH (mm)	450	460	470	480	490	500	510	520	530
L				❑	❑	❑	❑	❑	❑
M			❑	❑	❑	❑	❑		
S	❑	❑	❑	❑	❑				

	CODE	FSH	DESCRIPTION	TOTAL LENGTH	EUR €
❑	351	S	Frame short (S)	C-347=760mm, C-346=810mm	0,00
❑	352	M	Frame standard (M)	C-347=760mm, C-346=810mm	0,00
❑	353	L	Frame long (L)	C-347=810mm, C-346=860mm	0,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

03 Castor Wheels / Front Seat Height (FSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

Composite Castor Wheels

		Front Seat Height (FSH) in mm								
	Composite Castor Wheels	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
C-2480	4" (100x23mm) with integrated lighting	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00	❑ 130,00
C-151/908	4" (100x32mm) solid rubber black (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-151/909	4" (100x32mm) solid rubber grey (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-325/908	5" (125x40mm) solid rubber black (388g)		❑	❑	❑	❑	❑	❑	❑	❑
C-325/909	5" (125x30mm) solid rubber grey (318g)		❑	❑	❑	❑	❑	❑	❑	❑

Aluminium Castor Wheels (32mm)

		Front Seat Height (FSH) in mm								
	Aluminium Castor Wheels (32mm)	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
C-2481	4" (100x32mm) aluminium silver (281g)	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00
C-2482	5" (125x32mm) aluminium silver (363g)		❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00	❑ 216,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Aluminium Castor Wheels (37mm)

		Front Seat Height (FSH) in mm								
	Aluminium Castor Wheels (37mm)	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
C-2483	4" (100x37mm) silver (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2484	4" (100x37mm) black (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2485	4" (100x37mm) white (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2486	4" (100x37mm) red (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2487	4" (100x37mm) blue (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2488	4" (100x37mm) orange (210g)	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2489	5" (125x37mm) silver (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2490	5" (125x37mm) black (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2491	5" (125x37mm) white (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2492	5" (125x37mm) red (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2493	5" (125x37mm) blue (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00
C-2494	5" (125x37mm) orange (285g)		❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00	❑ 140,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Carbon Castor Wheels (30mm)

		Front Seat Height (FSH) in mm								
	Carbon Castor Wheels (30mm)	**450**	**4560**	**470**	**480**	**490**	**500**	**510**	**520**	**530**
C-2495	4" (100x30mm) black (158g)	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00
C-2496	5" (125x30mm) black (205g)		❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00	❑ 206,00

04 Rear Wheels / Rear Seat Height (RSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Rear Wheels (incl. Tyres and Push Rims)

Weight is indicated per complete wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
B		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT	EUR €
❑	752	A	Light-Wheel Schwalbe RightRun Light tyres (1" tyre width) Aluminium push rims, black	24"		376,00
❑	2473	A	Blacklight wheel, aluminium, rim/hub/spokes black Schwalbe Marathon Plus tyres (1" width) Aluminium push rims, black	24"		324,00
❑	2466	A	Cross wheel Knobby tyres (1.75" width) Stainless steel push rims	24"		476,00
❑	2461	A	DayLite wheel, aluminium, rim/hub/spokes black Gazelle tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	24"		366,00
❑	2468	B	DayLite wheel, aluminium, rim/hub/spokes black Speedlite tyres (1" width) Aluminium push rims, black *Maximum user weight 100kg*	25"		324,00
❑	2465	A	Six-Star High-pressure tyres (8bar) Aluminium push rims	24"		688,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear Wheels (without Tyres and Push Rims)

Tyres and push rims must be selected separately. Weight is indicated per wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490	500
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
B		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø	WEIGHT	EUR €
❑	651	A	Standard wheels, grey	24"	1465g	0,00
❑	2651	A	Standard wheels, black	24"	1465g	0,00
❑	848	A	Silverdesign, radial spokes, and high-flange hub	24"	870g	132,00
❑	695	A	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *NC with Carbolife push rims (C-849, C-850, C-853)*	24"		228,00
❑	695	B	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	25"		228,00
❑	695	C	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	26"		228,00
❑	2470	A	Spinergy LX, rim/hub and 12x4mm spokes black	24"	687g	864,00
❑	2471	A	Spinergy LX, rim/hub black, 12x4mm spokes white	24"	687g	864,00
❑	2472	A	Spinergy LX, rim/hub black, 12x4mm spokes orange	24"	687g	864,00
❑	2469	A	Spinergy CLX, carbon rim, hub/18x3mm spokes black	24"		1.188,00

05 Tyres

Tyres are made of a rubber compound that may leave permanent or hard-to-remove marks on certain surfaces (plastic, wood, parquet, carpets or rugs). No liability is accepted for abrasion damage. Weight is indicated per tyre.

	CODE	DESCRIPTION	Ø	WEIGHT	EUR €
❑	496	High-pressure tyre, 8 bar, 1" tyre width	24"		0,00
❑	897	Schwalbe Marathon Plus, puncture-resistant, 1" tyre width, black	24"/25"/26"	500g	86,00
❑	363	Schwalbe One, puncture-resistant, 1" tyre width, black	24"		122,00
❑	395	Maxxis VN Master Alpha Protect, 10 bar, puncture-resistant, 1" tyre width, black	24"/25"/26"		45,00

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

06 Push Rims

Weight is indicated per push rim.

	CODE	DESCRIPTION	Ø	WEIGHT	EUR €
❑	494	Aluminium, silver anodised ⚠ *NC with Active wheel (C-695)*	24"	344g	0,00
❑	487	Aluminium, black anodised	24"	255g	0,00
❑	493	Stainless steel, polished	24"/25"/26"		0,00
❑	445	Titanium ⚠ *NC with Silverdesign (C-848)* *NC with standard wheels (C-651, C-2651)*	24"/25"/26"	364g (24")	376,00
❑	168	Optigripp-special push rim for tetraplegics	24"		430,00
❑	849	Curve L, aluminium, black anodised, ergonomic profile ⚠ *NC with Active wheel (C-695)*	24"		442,00
❑	850	Curve L Tetra-Grip, aluminium, black, ergonomic profile with anti-slip coating ⚠ *NC with Active wheel (C-695)*	24"		442,00
❑	853	Gekko, aluminium, black anodised, ergonomic profile with integrated, replaceable silicone lip ⚠ *NC with Active wheel (C-695)*	24"		550,00
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*			146,00
❑	692	Push rim spacing, narrow			0,00
❑	693	Push rim spacing, wide			0,00

07 Rear Wheels Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	697	Release mechanism for tetraplegics, facilitates removal of the drive wheel ⚠ *Only with Silverdesign (C-848) or Active wheel (C-695)*		0,00
❑	489	Hand and spoke guard, transparent		184,00
❑	2082	Spoke reflectors		46,00
❑	819	Reflectors ⚠ *NC with rear wheels C-752, C-2473, C-2461, C-2468, C-2470, C-2471, C-2472*		18,40

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

08 Camber

	CODE	DESCRIPTION	EUR €
❑	423	1°	0,00
❑	447	3°	37,00
❑	454	6°	37,00

09 Center of Gravity

The measurement is taken from the rear edge of the backrest tube to the wheel axle centre, in millimetres. Further centre-of-gravity adjustments are possible in combination with the wheelbase extension (C-880).

	ACTIVE			MEDIUM			PASSIVE		
	1 (145mm)	2 (135mm)	3 (125mm)	4 (115mm)	5 (105mm)	6 (95mm)	7 (85mm)	8 (75mm)	9 (65mm)
Position	❑	❑	❑	❑	❑	❑	❑	❑	❑

Wheelbase Extension

Select the position of the axle tube in combination with the wheelbase extension (3 positions available; the desired centre of gravity is achieved in combination with the seat position). If a second axle tube is selected, also specify its position and the camber.

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	880	Wheelbase extension		426,00
❑	2998	Additional axle tube ⚠ *Only with wheelbase extension (C-880)*		292,00

☐ Please select by ticking the relevant boxes (S) Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Position Wheelbase Extension

The measurement is taken from the rear edge of the backrest tube to the wheel axle centre, in millimetres. The center of gravity setting is selected together with the wheelbase extension and the axle tube position.
The wheelbase extension features three positions. Position A corresponds to the standard axle tube position without wheelbase extension. If position B is selected, the axle tube is mounted in the second position; accordingly, position C uses the third position.
If a second axle tube is selected (only possible in position C), the center of gravity setting and the camber must additionally be specified. Please do not forget to select the center of gravity setting for the first axle tube in the previous selection.

	5 (105mm)	6 (95mm)	7 (85mm)	8 (75mm)	9 (65mm)	10 (55mm)	11 (45mm)	12 (35mm)	13 (25mm)	14 (15mm)	15 (5mm)	16 (-5mm)	17 (-15mm)
Pos. B	❑	❑	❑	❑	❑	❑	❑	❑					
Pos. C					❑	❑	❑	❑	❑	❑	❑	❑	❑

Camber (additional axle tube)

The camber of the additional axle tube must either be identical to the camber of the 1st axle tube or must not differ by more than 3°, e.g. 1° and 3° or 3° and 6°.

	CODE	DESCRIPTION	EUR €
❑		1°	0,00
❑		3°	0,00
❑		6°	0,00

10 Footplates

The difference between the front seat height (FSH) and the lower leg length (LLL) must be at least 50mm.

LLL (mm)	250	260	270	280	290	300	310	320	330	340	350	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510
A										❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
B	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑										

	CODE	LLL (mm)	DESCRIPTION	WEIGHT	EUR €
❑	311	A	Footrest, black aluminium, height adjustable ⚠ *NC with seat width > 460mm (C-48, C-350)*		0,00
❑	312	A	Footplate one-piece, black aluminium, height/depth and angle adjustable		0,00
❑	3532	B	High-mounted one-piece footplate, black aluminium, height/depth and angle adjustable		299,00

ACTIVE

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Footplates Accessories

	CODE		WEIGHT	EUR €
❑	359	Calf strap		0,00

11 Backrest

The hydroformed backrest tube is characterized by high rigidity and an ergonomically optimized shape. The fold-down backrest enables one-hand operation and features an integrated double-lock function (locks when folded).

Backrest Height (RH)

The backrest cover is adjustable with hook-and-loop fasteners, and the back height can be adjusted ±60mm in 15mm increments.

	C-620	C-626	C-631	C-632	C-633
	250mm	300 mm	350mm	400 mm	450mm
Backrest height	❑	❑	❑	❑	❑

Backrest Angle

The backrest angle is measured relative to the seat surface: 90° = upright; <90° = tilted forward; >90° = tilted backward.

	Position A	Position B	Position C	Position D	Position E
	75°	80°	85°	90°	95°
Backrest Angle	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Upholstery

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	235	Textile, black		0,00
❑	292	Mesh fabric, breathable, black		158,00
❑	593	Without backrest cover		0,00

Backrest Upholstery Options

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	2002	Backrest upholstery, 20mm wider		0,00
❑	2003	Backrest upholstery, 40mm wider		0,00

Backrest Accessories

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	2032	ErgoSeat Pro thoracic pads, small, pair		304,00

12 Ride® Backs

Please specify the CODE from the RIDE order sheet:

13 Push Handles

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	411	Without push handles		0,00
❑	413	Push handles, short		0,00
❑	410	Push handles, long		0,00
❑	141	Push handles, swiveling ⚠ *NC with RH 250mm (C-620)*		214,00
❑	502	Height-adjustable push handles, mounted on back tube, steplessly adjustable up to 150mm ⚠ *NC with backrest height < 350mm (C-620, C-626)* *The maximum achievable height with height-adjustable push handles is HSH + 540mm*		260,00

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

14 Arm Supports and Arm Pads

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Weight is indicated per item.

	CODE	
❑	624	*Montiercode bei HSH 390 - 430 mm ⚠ *nur i.V. mit HSH 390 - 430 mm*

Clothes and Mudguards

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	304	Clothes guard, carbon, fixed-mounted		206,00
❑	101	Mudguards, plastic, fixed-mounted		0,00
❑	783	Mudguards, carbon, fixed-mounted		484,00
❑	100	Mudguards, aluminium, fixed-mounted		292,00

Armrests

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	748	Armrests, height-adjustable (with screws), with black aluminium side guards with cold-protection insert (black plastic film), fixed-mounted		304,00
❑	24	Tubular armrest with foam rubber pad, aluminium black, swing-away (side), removable, height-adjustable (with tools), non-locking		246,00

15 Seat Cushions

Standard hook-and-loop strips are included on the seat upholstery.

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	560	Seat cushion, 30mm		120,00
❑	561	Seat cushion, 60mm		120,00
❑	7199	Netti Contour, breathable 3D cover		180,00
❑	7195	Seat cushion Netti Precision Active with Easycare+		650,00
❑	7196	Seat cushion Netti Precision Active with Stella+		650,00

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Seat Upholstery Options

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	833	Safety belt (metal buckle)		73,00

16 Ride® Seat Cushions

Please specify the CODE from the RIDE order sheet:

17 Brakes

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	305	Pressure brake (push to lock)		0,00
❑	2595	Light pressure brake, aluminium		152,00

Brake Options

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	681	Brake lever extension, foldable ⚠ *Only with pressure brake (C-305)*		61,00

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

18 Options

Anti-tippers

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	728	Anti-tippers, pair, swing-away ⚠ *NC with seat width < 360mm (C-32, C-34)* *NC with tipping aid (C-309)*		316,00
❑	729	Anti-tipper, left, swing-away ⚠ *NC with tipping aid (C-309, C-4930)*		158,00
❑	730	Anti-tipper, right, swing-away ⚠ *NC with tipping aid (C-309, C-4931)*		158,00

Tipping Aid


	CODE	DESCRIPTION	WEIGHT	EUR €
❑	309	Tipping aid, pair ⚠ *NC with anti-tippers (C-728, C-729, C-730)*		130,00
❑	4930	Tipping aid, left, swing-away ⚠ *NC with anti-tippers (C-728, C-729)*		65,00
❑	4931	Tipping aid, right, swing-away ⚠ *NC with anti-tippers (C-728, C-730)*		65,00

Crutch holder

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	970	Crutch holder ⚠ *Only with tipping-aid (C-309, C-4930, C-4931)*		43,50

Xtrends Options

	CODE	DESCRIPTION	WEIGHT	EUR €
❑	962	Backpack "X-TREME"		60,00
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*		162,00
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*		232,00



10 Code 141




10 Code 410



08 Code 681



17 Code 729



08 Code 2595