SMART S

2.370

Allowed user weight

150 kg

Suitable for passenger transport

Tested according to ISO 7176-19 (max. user weight 136 kg)



MEYRA GROUP



Optimised folding system with compact folding dimensions



Extremely low actuating forces



Individually adjustable
chassis



Unique side panel with height adjustable armrest, one handed operation

New Active Line

EFFICIENCY

- High part compatibility
- Little wear and proneness to repair through integral design of the frame and the quality of the attachment components
- Quick and long term assurance of spare parts provision through an area wide dealer structure

THERAPEUTIC BENEFIT

- Stabilization and mobilization of users with neurological diseases, through good support while sitting and low weight a.s.o.
- The straight front frame and swivel-away, removable leg supports make it easy to get close to everyday objects
- Folding mechanism for independent loading into a car
- Adaptable to functional changes of the user, e.g. by retrofitting electric drives
- Extensive equipment assortment for long-term users

FIELD OF USE

- For permanent and long term provision
- Very good suitability for many disease patterns, even for severely encumbered
- For users with remaining walking and standing abilities (standing transfer)
- With neurological diseases

● ORDER ○ COST ESTIMATE ○ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

Allowed user weight
150 kg

Suitable for passenger transport
Tested according to ISO 7176-19 (max. user weight 136 kg)

Hints
Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2026 – 31.12.2026.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

ACTIVE

Technical specifications

1) When using auxiliary drives, the permissible total weight must not be exceeded

Seat widths in mm	320/340/360/380/400/420/440/460/480/500/520
Width ready to drive in mm from	Seat width + 180
Width folded in mm from	280 with 0° wheel camber or 330 with 3° wheel camber
Seat depth in mm	380/400/420/440/460/480/500
Seat height front/rear in mm	400 to 540/370 to 530
Overall height in mm	Rear seat height + back support height
Back support height in mm	variable from 250 to 500 +25 mm
Arm support height in mm	ca. 170 - 245
Length with footrest in mm	880 - 1030 (depending on frame length, wheel size and axle position)
User weight	150 kg
Empty weight from	from 10.5 kg
Permitted total weight in kg	170 kg [1)]
Transport weight	6,5 kg
Rear wheel	560mm (22") / 600 mm (24") / 635 mm (25") / 660 mm (26")
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

01 Frame shape / seat width / seat depth

	Frame short 79° (C-351)			Frame medium 79° (C-352)		Frame long 79° (C-353)	
	(C-368)	(C-615)	(C-784)	(C-618)	(C-619)	(C-787)	(C-792)
Seat width/Seat depth	**SD 380 mm**	**SD 400 mm**	**SD 420 mm**	**SD 440 mm**	**SD 460 mm**	**SD 480 mm**	**SD 500 mm**
SW 320 mm (C-32)	❑	❑	❑	❑	❑	❑	❑
SW 340 mm (C-34)	❑	❑	❑	❑	❑	❑	❑
SW 360 mm (C-36)	❑	❑	❑	❑	❑	❑	❑
SW 380 mm (C-38)	❑	❑	❑	❑	❑	❑	❑
SW 400 mm (C-40)	❑	❑	❑	❑	❑	❑	❑
SW 420 mm (C-342)	❑	❑	❑	❑	❑	❑	❑
SW 440 mm (C-344)	❑	❑	❑	❑	❑	❑	❑
SW 460 mm (C-46)	❑	❑	❑	❑	❑	❑	❑
SW 480 mm (C-48)	❑	❑	❑	❑	❑	❑	❑
SW 500 mm (C-350)	❑	❑	❑	❑	❑	❑	❑
SW 520 mm (C-952)	❑	❑	❑	❑	❑	❑	❑

including utensil pocket under the seat belt

Variable block

	CODE	DESCRIPTION	TOTAL WIDTH
❑	992	Varioblock for additional drives	+ 20 mm

⚠ *ALBER drives only in combination with C-81 side panel with short armrest or C-84 side panel with long armrest*
Only in combination with 0° camber, C-423

ACTIVE

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

03 Front seat height (FSH) in combination with castor wheel (without seat cushion)

The maximum permissible seat height difference between the front and rear seat height is 90 mm

		Front Seat Height (FSH) in mm													
Code	**Castor**	**400**	**410**	**420**	**430**	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**
151/908	Ø 100 Solid rubber black	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑				
151/909	Ø 100 Solid rubber grey	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑				
325/908	Ø 125 Solid rubber black		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
325/909	Ø 125 Solid rubber grey		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
327/908	Ø 142 Soft solid rubber black			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
327/909	Ø 142 Soft solid rubber grey			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
645	Ø 180 Pneumatic tires						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
161	Ø 180 Solid rubber						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Front seat height (FSH) in combination with castor wheel (without seat cushion)

		Front Seat Height (FSH) in mm											
Code	**Castor**	**400**	**410**	**420**	**430**	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**
2480	Ø 100 x 23 Lightwheel black	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2481	Ø 100 x 32 Castor aluminum silver	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2482	Ø 125 x 32 Castor aluminum silver		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ *Tyres: CODE 2480 solid rubber, transparent/colored - CODE 2481/2482 solid rubber black*

Seat height front in combination with carbon castor (without seat cushion)

		Front Seat Height (FSH) in mm											
Code	**Castor**	**400**	**410**	**420**	**430**	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**
2495	Ø 100 x 30 mm, Black	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2496	Ø 125 x 30 mm, Black		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

⚠ *Tyres: solid rubber, black*

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Seat height front in combination with aluminium castor (without seat cushion)

		Front Seat Height (FSH) in mm											
Code	**Castor**	**400**	**410**	**420**	**430**	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**
2483	Ø 100 x 37 mm, Silver	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2484	Ø 100 x 37 mm, Black	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2485	Ø 100 x 37 mm, White	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2486	Ø 100 x 37 mm, Red	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2487	Ø 100 x 37 mm, Blue	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2488	Ø 100 x 37 mm, Orange	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
2489	Ø 125 x 37 mm, Silver		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
2490	Ø 125 x 37 mm, Black		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
2491	Ø 125 x 37 mm, White		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
2492	Ø 125 x 37 mm, Red		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
2493	Ø 125 x 37 mm, Blue		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
2494	Ø 125 x 37 mm, Orange		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Tyres: solid rubber, black

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Castor wheel option

	CODE	DESCRIPTION
❑	903	Reinforced castor forks
❑	2144	Reinforced castor fork connection ⚠ *recommended when using additional drives*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

04 Rear wheels i.c. with seat height (tires CAT 07 and hand rims CAT 06)

The maximum permissible seat height difference between the front and rear seat height is 90 mm

RSH (mm)	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530
A				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑			
B	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑						
D						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
E							❑	❑		❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø
❑	651	B	Standard wheel, incl. quick release axle (pair)	22"
❑	706	B	Drum braked wheel with radial spokes and drum brake for accompanying person ⚠ *Only in conjunction with 0° wheel camber CODE 423* *Only in conjunction with push handles CODE 412 or 502* *Wheel covering CODE 98 is recommended.*	22"
❑	651	A	Standard wheel, incl. quick release axle (pair)	24"
❑	2651	A	Standard wheel black, incl. quick release axle (pair)	24"
❑	706	A	Drum braked wheel with radial spokes and drum brake for accompanying person ⚠ *Only in conjunction with push handles CODE 412 or 502* *Wheel overlap CODE 98 is recommended.*	24"
❑	848	A	SILVERDESIGN with radial spokes and high flange rim incl. quick-release axle (pair)	24"
❑	695	A	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black	24"
❑	695	D	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black	25"
❑	695	E	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black	26"
❑	2469	A	Spinergy CLX, carbon rear wheel, spokes and hub black	24"
❑	2470	A	Spinergy LX, aluminum rear wheel, spokes, rim and hub black	24"
❑	2471	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes white	24"
❑	2472	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes orange	24"

⚠ *Spinergy wheels not in combination with PU-tyres (C-474, 902)*
Active wheels recommended for user weights > 100kg or dynamic drive
Active wheels not in combination with Carbolife oush rims (C-849, 850, 853)
Active wheels not in combination with PU-tyres (C-474, 902)

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear wheel i.c. with seat height (incl. tyre and handrim)

The max permissible seat height difference between front and rear seat height is 100 mm!

RSH (mm)	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
B	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑					
C					❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
D						❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	RSH	DESCRIPTION	Ø
❑	752	B	Lightwheel incl. RightRun Light tyres and aluminum handrim black	22"
❑	2465	A	Six-Star incl. 8 bar high pressure tyres and aluminium handrim	24x1"
❑	752	A	Lightwheel incl. RightRun Light tyres and aluminum handrim black	24"
❑	2466	C	Cross-Rad incl. coarse studded tyres and stainless steel handrims (pair)	24x1.75"
❑	2461	A	Day-Lite aluminium drive wheel, black rim, hub and spokes, black aluminium handrim and black MBL Gazelle tyres. *max. user weight 100kg*	24x1"
❑	2468	D	Day-Lite aluminum rear wheel, black rim, hub and spokes, black aluminum handrim and black MBL Speedlite tyres. *max. user weight 100kg*	25x1"
❑	2473	A	Blacklight aluminum rear wheel, incl. Schwalbe Marathon Plus tyres and aluminum push rims, rim, hub and spokes black	24x1"

Complete wheels - please do not select handrims and tyres!

05 Horizontal rear wheel position (center of gravity)

	ACTIVE (Pos. - mm)			MEDIUM (Pos. - mm)		PASSIV (Pos. - mm)	
	1 - 100**	2 - 90**	3 - 80	4 - 70	5 - 60	6 - 50	7 - 40
Position	❑	❑	❑	❑	❑	❑	❑

Measurement: Centre of back tube to centre of axle in mm
Drive wheel position 1 and 2 cannot be fitted in conjunction with frame short CODE 351

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Rear wheel options

	CODE	DESCRIPTION
❑	697	Release mechanism for tetraplegics, facilitates removal of the drive wheel ⚠ *Only i.C. with CODE 848 or CODE 695 drive wheel*
❑	423	0° wheel camber (track adjustable, wheel camber can be altered subsequently)
❑	447	3° wheel camber (track adjustable, wheel camber can be altered subsequent-ly) in combination with drum brake CODE 706 restricted seat height variation

06 Handrims and handrim options

	CODE	DESCRIPTION
❑	445	Titanium, with 6 brackets ⚠ *Only i.C. with active wheel CODE 695 and Spinergy wheel CODE 2469, 2470, 2471, 2472*
❑	493	Stainless steel, polished
❑	494	Aluminium, silver anodised ⚠ *Not in combination with active wheel CODE 695*
❑	168	Optigripp-special push rim for tetraplegics
❑	849	Curve L, aluminum black anodised, ergonomic handrim profile, H 31 mm ⚠ *NC with Active wheel (C-695)*
❑	850	Curve L Tetra Grip, anti-slip coated, aluminum, suitable for quadriplegics, ergonomic handrim profile, H 31 mm ⚠ *NC with Active wheel (C-695)*
❑	853	Gekko, aluminum black anodized with replaceable ruber lip, ergonomic hand rim profile, H 31mm ⚠ *NC with Active wheel (C-695)*
❑	871	One-arm drive for seat widths up to 480mm ⚠ *Only in conjunction with PU tyres CODE 902* *Not in conjunction with drum brakes CODE 706* *not suitable for very active use*

Push Rim Options

	CODE	DESCRIPTION	Ø	Ø
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*	22"	24"
❑	692	Handrim distance narrow		
❑	693	Handrim distance far		

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

07 Tyres

	CODE	DESCRIPTION	Ø
❑	474	PU tyre, puncture-proof, 1" tyre width, black ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24x1"
❑	486	Pneumatic tires 4 bar	22x1 3/8" - 24x1 3/8"
❑	496	Pneumatic tires 8 bar	22x1" - 24x1"
❑	902	PU tyre, puncture-proof, 1" tyre width, grey ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	22x1" - 24x1"
❑	902	PU tyre, puncture-proof, 1" tyre width, grey ⚠ *Not in combination with active wheel CODE 695*	22x1 3/8" - 24x1 3/8"
❑	897	Marathon-Plus-Evolution tyres, puncture protected	22x1" - 24x1"
❑	363	Schwalbe ONE tyre, no profile, puncture resistant	22x1" - 24x1"
❑	395	Maxxis VN Master Alpha Protect tyre black, puncture resistant, 10 bar	22x1" - 24x1" - 25x1" - 26x1"

⚠ *Tyres consist of a rubber compound which may leave permanent marks or be hard to remove from some surfaces (e.g. plastic, wooden or parquet flooring, rugs and carpets).*
We cannot accept liability for any abrasion damage to flooring.

08 Brakes

	CODE	DESCRIPTION
❑	305	Pressure brake (push to lock)
❑	60/650	One-hand pressure brake left (incl. Brake lever long, hinged)
❑	74/650	One-hand pressure brake right (including brake lever long, hinged)
❑	681	Brake lever extension, foldable, fixed-mounted
❑	986	Attachable brake lever extension ⚠ *NC with one-arm brake (C-650)*

09 Backrest height (BH)

	Backrest height in mm					
	(C-620)	(C-626)	(C-631)	(C-632)	(C-633)	(C-637)
DESCRIPTION	**250**	**300**	**350**	**400**	**450**	**500**
Tension adjustable back (via Velcro straps adjustable +25 mm)	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest variants

	CODE	DESCRIPTION
❑	2002	Back cover 20 mm wider ⚠ *only i.c. with CODE 235 textile black or 292 mesh, breathable, black*
❑	2003	Back cover 40 mm wider ⚠ *only i.c. with CODE 235 textile black or 292 mesh, breathable, black*
❑	593	Without backrest cover ⚠ *recommended when using RIDE back systems*

Back strap colours (seat strap always in black)

	CODE	DESCRIPTION
❑	235	Textile black
❑	292	Mesh fabric, breathable, black
❑	296	Net fabric, breathable , red

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

10 Backrest

	CODE	DESCRIPTION
❑	410	Back rest with push handle, short
❑	412	Backrest with push handle, long
❑	141	Push handles, swiveling ⚠ *only i.c. with Back without lumbar curve CODE 621*
❑	502	Backrest with push handle mounted to the frame tube, continuously height adjustable to 150 mm ⚠ *Not in combination with push handle code 140/141*
❑	140	Push handle integrated in the back tube, height adjustable up to 100 mm ⚠ *NC with backrest with lumbar support (C-622))* *NC with backrest height 250mm (C-620)*
❑	238	Folding push bar ⚠ *Not i.c. with push handles CODE 502*

Backrest options

	CODE	DESCRIPTION
❑	29	Backrest, angle-adjustable from seat surface, +/-15° in 5° increments, can be adjusted subsequently ⚠ *from BH 300 mm* *only i.c. with push handle CODE 410 / 412* *Not i.c. with Lumbar bend Code 622* *Not i.c. with BH 250 mm* *not i.c with side panel bracket CODE 24*
❑	621	Backrest without lumbar support
❑	622	Backrest with lumbar support ⚠ *possible from BH 300 mm*
❑	2032	ErgoSeat Pro thoracic pads, small, pair ⚠ *Recommended at back height 300 - 400 mm*
❑	814	Horizontal push bar, stabilises the back support under heavy strain ⚠ *not in combination with push handles CODE 141. Recommended from SB 460*
❑	913	Head support, 300 mm continuously height adjustable ⚠ *only in combination with push bar CODE 814*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

12 Seat Cushions

	CODE	DESCRIPTION
❑	560	Seat cushion 30 mm
❑	561	Seat cushion 60 mm
❑	7199	Netti Contour Breathable 3D cover
❑	562	Velcro strip on seat belt

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

14 Arm Supports and Arm Pads

1 = fixed screwed 2 = swivel up 3 = detachable 4 = lockable 5 = height-adjustable armrest 6 = with wheel cover

	CODE	DESCRIPTION	FUNCTIONS
❑	100	Aluminum side panel in black with carbon inlay	1,6
❑	98	Aluminum side panel in black with carbon insert and 50 mm wheel coverage	1,6
❑	81	Side guard, armrest short, height adjustable with one hand operation ⚠ *Only with RSH > 440mm ; NC with 3° camber and drum brake*	2,3,4,5
❑	84	Side guard, armrest long, height adjustable with one hand operation ⚠ *Only with RSH > 430mm ; NC with 3° camber and drum brake*	2,3,4,5
❑	748	Aluminium side panel in black with carbon insert, including height adjustable armrest. ⚠ *NC with light brake C-595 from rear seat height 440 mm*	1,5,6
❑	783	Carbon fiber side guard	1,6
❑	302	Light aluminium side panel in black. ⚠ *from the rear seat height 430 mm*	1

Side panel option

	CODE	DESCRIPTION
❑	24	Swing-away side panel bracket ⚠ *only i.c. with CODE 98, 100, 783 or without side panel* *not i.c. with back angle adjustable CODE 29*

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

15 Leg supports

	LLL (mm)	270	280	290	300	310	320	330	340	350	360
	A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE		DESCRIPTION	
❑	93		Removable, swing away	Pair
❑	759		Removable, swing away	Left
❑	760		Removable, swing away	Right
❑	92		Can be removed, moved away and swung up ⚠ *C-92 only with footplate C-798 and not in combination with frame short C-351*	Pair
❑	757		Can be removed, moved away and swung up ⚠ *Only with footplate C-798* *NC with short frame (C-351)*	Left
❑	758		Can be removed, moved away and swung up ⚠ *Only with footplate C-798* *NC with short frame (C-351)*	Right
❑	52		Amputee leg support	Pair
❑	4508		Amputee leg support	Left
❑	4507		Amputee leg support	Right
❑	293		Compact 78°	Pair
❑	3532	A	Shortened, can be removed, moved away and swung up ⚠ *only i.C. with leg rest compact CODE 293*	Pair 270-360 mm
❑	94		without leg rests	

⚠ *The difference between the seat height at the front and the lower leg length must be at least 50 mm*

ACTIVE

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Footrests

LLL (mm)	390	400	410	420	430	440	450	460	470	480	490
B	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	LLL	DESCRIPTION	depth
❑	312	B	Footplate one piece, black aluminium, flip up, height, depth and angle adjustable	
❑	315	B	Footrest continuous aluminum in black fold up, height and angle adjustable	
❑	798	C	Footrests divided, height adjustable, up-folding and height and angle adjustable ⚠ *from seat width 380 mm* *only i.C. with CODE 92 Legrests can be removed, swivelled away and upwards*	160 mm
❑	808	C	Footrests divided, up-folding, depth adjustable, height and angle adjustable	150 mm
❑	4313	B	LED footrest made of sturdy aluminum in black continuous, height / depth and angle adjustable ⚠ *From seat width 360 mm*	100 mm

⚠ *The difference between the seat height at the front and the lower leg length must be at least 50 mm*

Footrests options

	CODE	DESCRIPTION
❑	925	Operating aid for locking device, in case of limited hand function ⚠ *only in combination with upper leg support compact CODE 293*
❑	359	Calf belt

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

16 Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	224	Blue metallic
❑	227	Red metallic
❑	4044	Red matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4922	Metallic green
❑	4919	Silverline

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

17 Options hand and spoke protection

	CODE	DESCRIPTION
❑	489	Transparent ⚠ *Not i.c. with Spinergy Wheel CODE 2469, 2470, 2471, 2472*

Support castors

	CODE	DESCRIPTION
❑	691	Anti-Tip, 1 pair, swivelling (recommended) ⚠ *Not i.c. with step tube CODE 309*
❑	712	1 anti-tip, swivelling, mounted left ⚠ *Not in combination with pedal tube CODE 309/4930, not in combination with shunting castors CODE 746*
❑	713	1 anti-tip, swivelling, mounted right ⚠ *Not in combination with pedal tube CODE 309/4931, not in combination with shunting castors CODE 746*

Other accessories

	CODE	DESCRIPTION
❑	746	1 pair Micro castors, e.g. for tight spaces or in an aeroplane ⚠ *Not i.c.w. pedal tube CODE 309 or support castors CODE 691, from RSH 420 mm*
❑	833	Safety belt (metal buckle)
❑	970	Crutch holder
❑	819	Reflectors ⚠ *Not in conjunction with CODE 752, 2473, 2461 and 2468*
❑	309	Step tubes (1 pair)
❑	4930	1 step tube, mounted on the left ⚠ *not in combination with anti-tip-wheels, CODE 691/712 and anti-tip-wheels, CODE 746*
❑	4931	1 step tube, mounted on the right ⚠ *not in combination with anti-tip-wheels, CODE 691/713 and anti-tip-wheels, CODE 746*
❑		205542100 Hand compressor
❑	679	Folding lock

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Therapy tables

	CODE	DESCRIPTION
❑	929	Therapy table plastic, transparent, adjustable from 400-480 mm seat width ⚠ *only in combination with side panel CODE 84*
❑	930	Therapy table for self-drivers, plastic, transparent, slide-on for defined seat width ⚠ *only in combination with side panel CODE 84*

⚠ *With 24" wheels and a rear seat height of less than 470 mm, there is a resulting limitation in terms of armrest height with use of the therapy table Code 929/930*

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	
❑	2082	Spoke reflectors	



10 Code 29



15 Code 52



08 Code 73



14 Code 81




14 Code 84




15 Code 92



15 Code 93



14 Code 98



14 Code 100



10 Code 140




10 Code 141



10 Code 238



15 Code 293



14 Code 302



08 Code 305



15 Code 315



10 Code 410



10 Code 814



15 Code 4312



05 Code 423



05 Code 447



10 Code 621



10 Code 622



08 Code 650




08 Code 681



05 Code 697



14 Code 748



14 Code 783



15 Code 798



15 Code 808